Vinivas Institute of Technolog

CBCS SCHEME



1

2

3

4

15ME43

Fourth Semester B.E. Degree Examination, July/August 2022 Applied Thermodynamics

Time: 3 hrs.

Max. Marks: 80

Note: 1. Answer any FIVE full questions, choosing ONE full question from each module. 2. Use of thermodynamics data hand book allowed.

Module-1

- a. Derive an expression for the air standard efficiency of a diesel cycle with the help of P-V and T-S diagrams. (08 Marks)
 - b. Air enters the compressor of a gas turbine plant at 20°C and compressed with pressure ratio 3.5. The isentropic efficiency of the compressor is 80%. The air is then heated in a heat exchanger having 70% effectiveness. The maximum cycle temperature is 650°C. The isentropic efficiency of the turbine is 75%. Neglecting the losses find thermal efficiency of the cycle. Take R = 287J/kgK and $\gamma = 1.4$. (08 Marks)

OR

- a. Derive an expression for optimum pressure ratio for maximum specific power output in terms of maximum and minimum temperatures of the brayton cycle. (08 Marks)
 - b. An engine working on ideal otto cycle has a swept volume of 0.12m³ and clearance volume of 0.03m³. The pressure and temperature at the beginning of compression are 1 bar and 100°C. If the pressure at the end of constant volume heat addition is 25 bar, calculate : i) air standard efficiency ii) temperature and pressure at all salient points. (08 Marks)

Module-2

- a. What are the drawbacks of Carnot cycle as a reference cycle? (02 Marks)
 b. Explain with T S diagrams the effect of pressure and temperature on the Rankine cycle.
 - c. A Rankine cycle using water as the working fluid operates between the pressure limits of 10KPa and 15000KPa. The maximum temperature of the cycle is 600°C. Determine the cycle efficiency and the steam flow rate.

OR

- a. With neat sketch and T–S diagram, derive an expression for the thermal efficiency of a Rankine cycle with Reheat. (08 Marks)
 - b. Steam from a boiler enters a turbine at 25 bar and expands to condenser pressure of 0.2 bar. Determine the Rankine cycle efficiency neglecting pump work when, i) steam is 80% dry at turbine inlet ii) steam is saturated at turbine inlet. Inlet by 76.1°C. Take : T_s at 25 bar = 223.9°C, h_{sup} at 25 bar, 300°C = 3008.8 kJ/kg; s_{sup} = 6.644kJ/kgK. (08 Marks)

Module-3

- 5 a. Define the terms : i) Stoichiometric air ii) Enthalpy of formation iii) Combustion efficiency. (06 Marks)
 - b. During a test on single cylinder, four stroke oil engine, the following results were obtained.

Cylinder bars = 20cm, Stroke = 40cm, mean effective pressure = 6bar, Torque = 407 Nm, Speed = 250rpm, fuel consumption = 4 kg/h, C.V. of fuel = 43MJ/kg, Cooling water flow rate = 4.5 kg/min, air used = 30 kg/kg of fuel, Rise in temperature of cooling water = 45° C, Temperature of exhaust gases = 420° C, Room temperature = 20° C CP of exhaust gases = 1 kJ/kgK, CP of water = 4.18 kJ/kgK. Find IP, BP and draw heat balance sheet on hour basis. (10 Marks)

(06 Marks)

(04 Marks)

- a. Explain the factors affecting detonation. 6
 - b. Methane is burned with atmospheric air. The analysis of the products of combustion on a dry basis is as follows :

 $CO_2 = 10\%$, $O_2 = 2.37\%$, CO = 0.53% and $N_2 = 87.1\%$. Calculate the air fuel ratio and the percent theoretical air and determine the combustion equation. (10 Marks)

Module-4

- 7 Determine the terms : a. iii) Dew point temperature iv) Relative humidity. i) C.O.P ii) T.O.R (04 Marks) b. With a neat sketch explain vapour absorption refrigeration system. (06 Marks)
 - c. A vapor compression refrigerator of 10 tonnes capacity using Freon -12 as the refrigerant has an evaporator temperature of 10°C and a condenser temperature of 30°C. Assuming simple saturation cycle, determine : i) mass flow rate of refrigerant ii) C.O.P. Take CPV = 0.72 kJ/kgK.(06 Marks)

OR

- a. Mention any 4 properties of a good refrigerant. 8
 - b. With the help of psychrometric chart explain i) Sensible heating ii) cooling and dehumidifying. (04 Marks)
 - Atmospheric air at 101.325 KPa has 30°C DBT and 15°C DPT. Without using C. psychrometric chart, using the property values from the tables, calculate : i) Partial pressures of air and water vapour ii) Specific humidity iii) Relative humidity iv) Vapour density iv) Enthalpy of moist air. (08 Marks)

Module-5

- a. What are the advantages of multi-stage compression? 9 (04 Marks) b. Derive an expression for the optimum pressure ratio to get minimum work in case of a 2 stage reciprocating air compressor. (06 Marks) c. A single – stage double – acting air compressor is required to deliver 14m³ of air per minute measured at 1.013 bar and 15°C. The delivery pressure is 7 bars. Take clearance volume as
 - 5% of the swept volume and index of compression and expansion as n = 1.3. Calculate : i) Volumetric efficiency ii) Delivery temperature iii) Indicated power. (06 Marks)

OR

10 a. What are steam nozzles? How they are classified?

- b. What are the effects of super saturation in a nozzle?
- c. A single cylinder, double acting air compressor is required to deliver 100m³/min of air at a mean piston speed of 500m/min measured at 1 bar and 15°C. The air is delivered at 7 bar. Assume a clearance volume of $\frac{1}{15}$ th of swept volume per stroke. Find volumetric

efficiency, speed, bore, stroke for the following two cases.

- If ambient and suction conditions are same. 1)
- ii) If ambient and suction conditions are different.

Take : Ambient pressure	= 1 bar
Ambient temp	$= 15^{\circ}C$
Suction pr	= 0.98.bar
Suction temp	= 30°C
L/D	= 1.25.

(04 Marks)

(04 Marks)